









- :: Maintenance-free due to no brush
- :: Energy production is more efficient than brushed DC motor because of no friction loss caused by brushes, enabling to lower amperage for reduced heat production and increased work amount on a single full battery charge.







**Enhanced Dust and** Drip-resistant Performance ensure reliable operation even under bad weather.

#### **Extreme Protection Technology**





Lightweight -

Simple switch specifications

2-speed settings

3.0 kg

Battery: BL1850B

Variable speed

control by trigger

Run time\*

High

Battery: BL1850B

\*No load continuous run time (approx): min

## Optional Accessories

#### Nylon cutting head

Part No. 197296-3 Cord/Line: Ø2.0mmx3.0m Ref.: 90-M10L

Part No. 198893-8

Cord/Line: Ø2.0mmx3m Ref.: 95-M10L

Part No. 191D89-4

Cord/Line: Ø2.0mmx4m Ref.: 96-M10L



# Four-leaf spiral nylon cord

Green (Ø2.0mm)

Shape	length	Part No.
•	15m	E-01769
	30m	E-01775
	310m	E-01781

#### Standard nylon cord

Green (Ø2.0mm)

Shape	length	Part No.
	15m	E-02705
	126m	F_02711

#### **Shoulder strap** assembly

Single Part No.125516-5



## Portable Power Pack

PDC01



Powered by up to four 18V LXT batteries



### **Charging Time**

18V	DC18RC	DC18SD
<b>BL1815N</b> 1.5Ah	15 min	30 min
<b>BL1820B</b> 2.0Ah	24 min	45 min
<b>BL1830B</b> 3.0Ah	<b>22</b> min	60 min
<b>BL1840B</b> 4.0Ah	36 <sub>min</sub>	90 min
<b>BL1850B</b> 5.0Ah	45 min	110 min
<b>BL1860B</b> 6.0Ah	55 min	130 min

# **Cordless Grass Trimmer**

#### **DUR192LZ**

Variable Speed Brake **Electronic 2-Speed** Constant Speed Soft Start

**Cutting Width** No Load Speed (RPM) Spindle Size Max Run Time (min)

Sound Pressure Level Sound Power Level Vibration Level Dimensions (L x W x H)

300 mm (11-3/4") High / Low: 0 - 4,500 / 0 - 6,000 M10 x 1.25 LH

High / Low, w/ 300 mm (11-3/4") Nylon Cutting Head, w/ Load, w/ BL1850B: 18/34 High / Low, w/ 300 mm (11-3/4") Nylon Cutting Head, w/o Load, w/ Bl. 1850B: 46 / 97 74.8 dB(A)

87.8 dB(A)

07.0 aUry Front / Rear: 2.5 / 2.5 m/s² or less w/o Nylon Cutting Head, w/ BL1830B / BL1840B / BL1850B / BL1860B: 1,670 x 186 x 246 mm (65-3/4 x 7-3/8 x 9-11/16") w/o Nylon Cutting Head, w/BL1815N / BL1820B: 1.655 x 186 x 246 mm (65 x 7-3/8 x 9-11/16")

Net weight 2.7 - 3.0 kg (6.0 - 6.6 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area