





Max Run Time

45 min

Battery: BL1830B on a full battery charge / No load

Cutting Width

260 mm



Lightweight for reduced operator fatigue

Telescopic shaft pipe

- Well balanced design with fully adjustable features to suit any operator
- Adjustable in length from 1,248mm to 1,436mm.





can be more conveniently locked/released by changing the mechanism from the rotary type to the lever type.

Easy-to-operate front grip

Adjustable to a desired height by changing the angle and position.



Angle adjustment of motor head

The cutting angle can be adjusted in 5 steps.



Edger function

Using the grass trimmer as an edger is suitable for cutting the grass growing along the bricks or blocks.



The nylon cutting head has a bump and feed mechanism



Shoulder belt (Standard equipment)





Wire guard • reduces the

- reduces the risk of damaging fences, flowers or ornaments.
- used as auxiliary guide for edging



— ø1.65mm four-leaf nylon cord





mechanism

Optional Accessories Charging Time

Spool set MG

Part No. 191Y39-5



Four-leaf nylon cord

Blue	
Size	Part No.
Ø1.65mmx15m	E-01731
Ø1.65mmx30m	E-01747
Ø1.65mmx445m	E-01753

18V LUTTHIUMHON	DC18RC	DC18SD
BL1815N 1.5Ah	15 min	30 min
BL1820B 2.0Ah	24 _{min}	45 min
BL1830B 3.0Ah	22 min	60 min
BL1840B 4.0Ah	36 min	90 min
BL1850B 5.0Ah	45 min	110 min
BL1860B 6.0Ah	55 min	130 min

Cordless Grass Trimmer DUR193Z

Cutting Width
No Load Speed (RPM)
Max Run Time (min)
Sound Pressure Level
Sound Power Level
Vibration Level
Dimensions (L x W x H)

W/Nylon Cutting Head, w/BL1815N/BL1820B
: 1,238 - 1,427 x 265 x 358 mm
(48-3/4 - 56-1/4 x 10-3/8 x 14-1/8")
W/Nylon Cutting Head, w/BL1815N/BL1840B/BL1850B/BL1860B
: 1,248 - 1,436 x 265 x 358 mm
(49-1/4 - 56-1/2 x 10-3/8 x 14-1/8")
Net weight

Trimmer Head: 260 mm (10-1/4")
7,800
W/BL1830B: 45
83.1 dB(A)
W/Nylon Cutting Head, w/BL1815N/BL1820B
: 1,248 - 1,436 x 265 x 358 mm
(49-1/4 - 56-1/2 x 10-3/8 x 14-1/8")
2.3 - 2.6 kg (5.1 - 5.7 lbs.)

The weight may differ depending on the attachment(s), including the battery cartridge. The lightest and heaviest combination, according to EPTA-Procedure 01/2014, are shown in the table. Items of standard equipment and specifications may vary by country or area.