



Accessories

Adapter pipe 85-72 set

Part No. 191L96-5



Flat nozzle set

Part No. 197889-6
Narrow profile improves air speed for removing heavier debris such as wet leaves



Gutter nozzle set

Part No. 191B03-8



Gutter nozzle set

Part No. 191B03-8



Band assembly set

Part No. 191J48-4



Portable Power Pack



PDC1200



Charger
DC4001
Charging time:
6 hours



Battery Powered



Adapter set

40Vmax

Part No.
191N62-4



Adapter between
Battery box of Portable
power pack and
Product on 40Vmax
XGT platform

18Vx2

Part No.
191J51-5



Adapter between
Battery box of Portable
power pack and
Product on 18Vx2 LXT
platform

18V

Part No.
191J50-7



Adapter between
Battery box of Portable
power pack and Product
on 18V LXT platform
*PDC01 only

PDC01



Powered by up
to four 18V LXT
batteries



Portable Power Pack

PDC1200 / PDC01

	PDC1200	PDC01
Capacity	33.5 Ah	24 / 12 Ah
Energy Capacity	1,206 Wh	432 Wh
Number of Cells	100	-
Charging Time (hours)	6	-
Dimensions (L x W x H)	w/o Harness: 369 x 261 x 139 mm (14-1/2 x 10-1/4 x 5-1/2") w/ Harness: 428 x 261 x 164 mm (16-7/8 x 10-1/4 x 6-1/2")	400 x 195 x 132 mm (15-3/4 x 7-5/8 x 5-3/16")
Net weight*	8.8 kg (19.4 lbs.)	w/o battery: 2.8 kg (6.1 lbs.)

*not covered by EPTA-Procedure

Standard Equipment: PDC1200: Harness, Adapter for 36V (18V x2) [countries-specific], Charger

PDC01: Harness, Adapter [countries-specific]

Weight according to EPTA-Procedure 01/2014

Items of standard equipment and specifications may vary by country or area.



Portable Power Pack
PDC1200 / PDC01



Ideal for long hours of work

Continuous run time (approx)
on a full battery charge
with PDC1200

90 min

Variable speed control mode: 0-max

UB001C

Powerful blowing force

Max 20 N*

*Boost mode



WG
WET GUARD
PDC1200



Portable Power Pack
PDC01



Battery cover
protects batteries from water and dust.

Backpack harness
can be detached from the battery box, allowing for use as a stationary power pack.

Fuel gauge for each battery
indicates the battery status by two green lamps.

Main power switch
with auto-off function

Powered by up to four 18V LXT batteries



Height-adjustable waist belt
The position of the waist belt can be adjusted for personal fit and comfort.

1,200Wh high capacity

Portable Power Pack
PDC1200

Height-adjustable waist belt

The position of the waist belt can be adjusted for personal fit and comfort.



Quickly removable harness

can be attached/removed from the main unit with a single action.



Reflectors

keep operator visible from a distance even in the dark.



4-LED fuel gauge

indicates the battery status by four green LEDs.
(turns on with a push of the main power switch.)

**BL
MOTOR**



Variable speed control by trigger, with Cruise control lever

Cruise control lever allows you to lock the variable speed control trigger at a desired power level.



Best grip-to-frame angle

Stand



Low noise level

Smoother airflow, which is achieved by redesigning the position of controller and the air intake port, decreases noise while increasing blowing force.

Boost mode



- In Boost mode, 20N max blowing force is always available.
- Usage time of Boost mode is restricted to protect the machine.

Available operation time in boost mode, under environment temperature of 25°C

Battery	Available operation time	
	Time per run* ¹	Cumulative operation time* ²
PDC1200	5 min	60 min
PDC01 (BL1860Bx4)	5 min	17 min

*1 Max time per run is at least 30 seconds or longer and depends on usage environment.
*2 Total operation time when the machine was intermittently used in Boost mode only.

Battery Powered Blower
UB001C



36V high power drive system using the Makita portable power pack

Up to four batteries can be carried on user's back, enabling long continuous operation while providing more lightweight tool body.

Less user fatigue as well as more powerful air flow

Nozzle is designed so that its end points downward. This small change can displace the reaction force towards the handle side to minimize the return tilting action of the machine, reducing user's arm fatigue.



3-stage telescopic long nozzle with an adjustment range of 100mm (4")



WG
WETGUARD UB001C / PDC1200 only

High water-resistance allows to operate the machine even if it is wet with water.

